

# Theme Customization Controls

Download the PDF of this article.

## In this Article

## Related Articles

### Overview

This document outlines the standardized controls used in FormAssembly themes. You have 36 options to control within the form builder, but if you'd like to stylize your form even more, you can use the controls below along with your CSS knowledge to accomplish this.

**Please Note:** Our Support team cannot support or write custom CSS code.

---

## Controls and Selectors

### LOGO

Name of Control	Description of Control	Selectors
Logo Image	Allows for a logo image upload. Logo is placed in the page header, above the form.	.wFormContainer .wFormHeader
Logo Size	Logo image size. Image size is set by the width and scales proportionately.	.wFormContainer .wFormHeader

	User can enter a numerical value in the text input, and then select a scaling unit (ex. px, em, rem, etc.)	
Logo Position	Horizontal positioning of the logo image. Choices include left, center, and right.	.wFormContainer .wFormHeader

## BACKGROUND

Name of Control	Description of Control	Selectors
Background Color	Background color of the page, behind the form.	.wFormWebPage
Form Background Color	Background color of the form	.wFormContainer .wForm, .reviewHeader, .reviewResponse, .reviewFooter, .wForm .field-hint- inactive .hint, .wForm .hintsBelow .field-hint, .wform .hintsSide .field-hint
	Background color of the pop-up calendar (found on date inputs)	html .kalendae
Form Header Background Color	Background color of the form header. (Background of the form title)	.wFormContainer .wForm .wFormTitle
	Text color of the links in the	.wFormContainer

	<p>page footer (ex. "Contact Information" and "Your Rights Under GDPR")</p> <p>Exceptions</p> <p>    Lightning - Footer links controlled by Input Text Color control</p> <p>    Polar and Tag - Footer link color controlled by Link Text Color control</p>	<p>.wFormFooter</p> <p>.supportInfo a,     .wFormContainer</p> <p>.wFormFooter</p> <p>.supportInfo a:hover</p>
--	---	--

## BORDERS

Name of Control	Description of Control	Selectors
Form Border Color	Color of the form border. If no border is desired a color with 0 opacity can be chosen.	.wFormContainer .wForm, .reviewHeader, .reviewResponse
Form Fieldset Border Color	Color of the fieldset border	.wFormContainer fieldset
	Color of the emphasized fieldset border	.wFormContainer fieldset.highlighted
	Color of input borders on focus (when the form respondent has	.wFormContainer .wForm .inputWrapper textarea:focus, .wFormContainer .wForm .inputWrapper textarea.required:focus,

	<p>clicked into the input)</p>	<pre> .wFormContainer .wForm .inputWrapper input[type='text']:focus, .wFormContainer .wForm .inputWrapper input[type='text'].required:focus, .wFormContainer .wForm .inputWrapper input[type='password']:focus, .wFormContainer .wForm .inputWrapper input[type='password'].required:focus, .wFormContainer .wForm .inputWrapper select:focus, .wFormContainer .wForm .inputWrapper select.required:focus </pre>
--	--------------------------------	--

## TITLE

<b>Name of Control</b>	<b>Description of Control</b>	<b>Selectors</b>
Title Font	Font-family of the form title	.wFormContainer .wForm .wFormTitle
Title Font Size	Font-size of the form title. User can enter a numerical value in the text input, and then select a scaling unit (ex. px, em, rem, etc.)	.wFormContainer .wForm .wFormTitle
Title Text Color	Color of the form title	.wFormContainer .wForm

.wFormTitle

## SECTION

<b>Name of Control</b>	<b>Description of Control</b>	<b>Selectors</b>
Section Title Font	Font-family for page titles within multi-page forms	.wFormContainer .wForm .section.pageSection > h4, .wFormContainer .wForm .htmlSection h4, .wForm div.section > .preField
	Font-family for section titles within forms	.wFormContainer .wForm .section.pageSection > h4, .wFormContainer .wForm .htmlSection h4, .wForm div.section > .preField
	Font-family for fieldset legends (titles) within forms	#wFormResumePage legend, #responsePasswordResetform legend, .wFormContainer fieldset legend{
Section Title Font Size	Font-size for page title within multi-page forms. User can enter a numerical value in the text input, and then select a scaling unit	.wFormContainer .wForm .section.pageSection > h4, .wFormContainer .wForm .htmlSection h4, .wForm div.section >

	(ex. px, em, rem, etc.)	.preField
	Font-size for section titles within forms. User can enter a numerical value in the text input, and then select a scaling unit (ex. px, em, rem, etc.)	.wFormContainer .wForm .section.pageSection > h4, .wFormContainer .wForm .htmlSection h4, .wForm div.section > .preField
	Font-size for fieldset legends (titles) within forms. User can enter a numerical value in the text input, and then select a scaling unit (ex. px, em, rem, etc.)	#wFormResumePage legend, #responsePasswordResetform legend, .wFormContainer fieldset legend{
Section Title Text Color	Text color for page title within multi-page forms	.wFormContainer .wForm .section.pageSection > h4
	Text color for section title within forms	.wFormContainer .wForm .htmlSection h4
	Text color for fieldset legends (titles) within forms	#wFormResumePage legend, #responsePasswordResetform legend, .wFormContainer fieldset legend{
	Text color of the month and year of the pop-up calendar	html .kalendae .k-calendar .k-caption
	Text color of the Previous/Next Month/Year icon links in the pop-up	html .kalendae .k-calendar .k-btn-previous-month, html .kalendae .k-

	calendar	calendar .k-btn-next-month, html .kalendae .k- calendar .k-btn-previous- year, html .kalendae .k- calendar .k-btn-next-year, html .kalendae .k- calendar .k-btn-previous- month: hover, html .kalendae .k- calendar .k-btn-next- month: hover, html .kalendae .k- calendar .k-btn-previous- year: hover, html .kalendae .k- calendar .k-btn-next- year: hover
--	----------	--

## FONTS

<b>Name of Control</b>	<b>Description of Control</b>	<b>Selectors</b>
Main Font	Font-family of all body copy/paragraph text	.wFormContainer, .htmlSection .htmlContent span, .htmlSection .htmlContent
	Font-family of all input labels	.wFormContainer .label, .oneField .label

		span
	Font-family of the pop-up calendar	html .kalendae
Main Text Size	Font-size of all body copy/paragraph text	.wFormContainer, table
	Font-size of all input labels	
	Font-size of all input text	
Main Text Color	Text color of all body copy/paragraph text	.wFormContainer .wForm, .reviewHeader, .reviewResponse, .reviewFooter, .htmlSection .htmlContent span, .htmlSection .htmlContent, .wFormContainer fieldset > fieldset:last-child, .wFormContainer table.matrixLayout thead tr.headerRow th, .wFormContainer table.gridLayout thead tr.headerRow th, .wFormContainer table.matrixLayout tbody tr th.headerCol, .wFormContainer table.gridLayout



	tbody tr th.headerCol
Text color of all input labels	<pre>.label,\n .wFormContainer .label,\n .wFormContainer .label.preField,\n .wFormContainer .oneChoice .label.postField,\n .oneField .label span,\n .wFormContainer .wForm .inputWrapper input[type='file'] "}"&gt;.wFormContainer .group &gt; .label, .wFormContainer .label, .wFormContainer .label.preField, .wFormContainer .oneChoice .label.postField, .oneField .label span, .wFormContainer .wForm .inputWrapper input[type='file']</pre>
Text color of the days of the pop-up calendar	<pre>html .kalendae .k- calendar .k-title, html .kalendae</pre>

		.k-calendar .k-header, html .kalendae .k-calendar .k-days, html .kalendae .k-calendar .k-header span
	Text color of the out-of-month dates (dates outside of the currently selected month)	html .kalendae .k-calendar .k-days span.k-out-of-month
Link Text Color	Color of all links that occur within the form.	.wFormContainer a, .wFormContainer a:hover, .wForm :link, .wFormContainer .duplicateSpan a
	Exceptions Polar and Tag Themes Only - Text color of the links in the page footer (ex. "Contact Information" and "Your Rights Under GDPR")	.wFormContainer .wFormFooter .supportInfo a, .wFormContainer .wFormFooter .supportInfo a:hover
Hint Text Color	Text color of the character count	.wFormContainer .lengthIndicator
	Text color of the word count	.wFormContainer .count-words
	Text color of hint text	.wForm .field-hint-inactive .hint, .wForm .hintsBelow .field-

		hint, .wform .hintsSide .field-hint
--	--	---

## ERRORS

Name of Control	Description of Control	Selectors
Error Color	Color of the Required Field markers	.wFormContainer .reqMark:after
	Border color of the field input border for fields that have an error on form submit	.wFormContainer .oneField.errFld .inputWrapper input[type='text'], .wFormContainer .oneField.errFld .inputWrapper input[type='password'], .wFormContainer .oneField.errFld .inputWrapper textarea, .wFormContainer .oneField.errFld .inputWrapper select, .wFormContainer .oneField.errFld .inputWrapper input[type="text"].required
	Text color of the field error message for fields that have an error on form submit	.wFormContainer .oneField.errFld div.errMsg
	Border color of the	.wfTab.wfTabCurrentPage.errMsg,

	navigation tab for page(s) that contain field error(s) on form submit	.wfTab.errMsg
	Text color of form error messages, located at the top of the page	.errorMessage, a.errMsg

## INPUTS

Name of Control	Description of Control	Selectors
Input Border Radius	Border radius of the Review Page Header, Responses, and Footer Sections	.reviewHeader, .reviewResponse, .reviewFooter
	Border radius of all inputs	.saveAndResume input[type='text'], .saveAndResume input[type='password'], .required, .wFormContainer .wForm .inputWrapper input[type='text'], .wFormContainer .wForm .inputWrapper input[type='password'], .wFormContainer .wForm .inputWrapper select, .wFormContainer .wForm .inputWrapper textarea

	Border radius of fieldset borders	.wFormContainer fieldset
	Border radius of all buttons	.wFormContainer .actions .primaryAction, .wFormContainer .actions .primaryAction:disabled, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
	Border radius of page navigation tabs (Exceptions: Does not apply to Demo, Lightning, and Polar themes)	.wFormContainer .wfTab, .wFormContainer .wfTab:hover
Input Text Font	Font-family for all input text	.saveAndResume input[type='text'], .saveAndResume input[type='password'], .required, .wFormContainer .wForm .inputWrapper input[type='text'], .wFormContainer .wForm .inputWrapper input[type='password'], .wFormContainer .wForm .inputWrapper select, .wFormContainer .wForm .inputWrapper textarea, .wFormContainer .wForm .inputWrapper select option, .wFormContainer .wForm

		<pre> .inputWrapper input:not([type="file"]):read-only,     .wFormContainer .wForm .inputWrapper textarea:read-only,     .wFormContainer .wForm .inputWrapper input:not([type="file"]):-moz-read- only,     .wFormContainer .wForm .inputWrapper textarea:-moz-read- only,     .wform .readonly </pre>
<p>Input Text Color</p>	<p>Text color for all input text</p>	<pre> .input-radio-faux::before,\n .wFormContainer .wForm .inputWrapper input[type=\"checkbox\"]:checked + .label &gt; .input-checkbox- faux::before,\n .tt- menu\"}\"&gt;.saveAndResume input[type='text'],     .saveAndResume input[type='password'],     .required,     .wFormContainer .wForm .inputWrapper input[type='text'],     .wFormContainer .wForm .inputWrapper input[type='password'],     .wFormContainer .wForm .inputWrapper select,     .wFormContainer .wForm .inputWrapper textarea,     .wFormContainer .wForm .inputWrapper textarea:focus,     .wFormContainer .wForm .inputWrapper textarea.required:focus, </pre>

		<pre> .wFormContainer .wForm .inputWrapper input[type='text']:focus, .wFormContainer .wForm .inputWrapper input[type='text'].required:focus, .wFormContainer .wForm .inputWrapper input[type='password']:focus, .wFormContainer .wForm .inputWrapper input[type='password'].required:focus, .wFormContainer .wForm .inputWrapper select:focus, .wFormContainer .wForm .inputWrapper select.required:focus, .wFormContainer .wForm .inputWrapper .oneChoice .input- checkbox-faux:before, .wFormContainer .wForm .inputWrapper input[type="radio"]:checked + .label &gt; .input-radio-faux::before, .wFormContainer .wForm .inputWrapper input[type="checkbox"]:checked + .label &gt; .input-checkbox-faux::before, .tt-menu </pre>
	<p>Exceptions Lightning only - Text color of the links in the page footer</p>	<pre> .wFormContainer .wFormFooter .supportInfo a, .wFormContainer .wFormFooter .supportInfo a:hover </pre>
Input	Background color	.input-radio-faux::before,\n

Background Color	for all inputs	<pre> .wFormContainer .wForm .inputWrapper input[type="checkbox"]:checked + .label &gt; .input-checkbox- faux::before,\n .wFormContainer .wfAutosuggest.tt-input,\n .tt- menu"}"&gt;.saveAndResume input[type='text'],     .saveAndResume input[type='password'],     .required,     .wFormContainer .wForm .inputWrapper input[type='text'],     .wFormContainer .wForm .inputWrapper input[type='password'],     .wFormContainer .wForm .inputWrapper select,     .wFormContainer .wForm .inputWrapper textarea,     .wFormContainer .wForm .inputWrapper .oneChoice .input- checkbox-faux:before,     .wFormContainer .wForm .inputWrapper input[type="radio"]:checked + .label &gt; .input-radio-faux::before,     .wFormContainer .wForm .inputWrapper input[type="checkbox"]:checked + .label &gt; .input-checkbox-faux::before,     .wFormContainer .wfAutosuggest.tt-input,     .tt-menu </pre>
Input	Border color for	<pre> .input-radio-faux::before,\n </pre>



Border  
Color

all inputs

```
.wFormContainer .wForm
.inputWrapper
input[type=\"checkbox\"]:checked +
.label > .input-checkbox-
faux::before,\n .wFormContainer
.wfAutosuggest.tt-
input"}">.saveAndResume
input[type='text'],
    .saveAndResume
input[type='password'],
    .required,
    .wFormContainer .wForm
.inputWrapper input[type='text'],
    .wFormContainer .wForm
.inputWrapper input[type='password'],
    .wFormContainer .wForm
.inputWrapper select,
    .wFormContainer .wForm
.inputWrapper textarea,
    .wFormContainer .wForm
.inputWrapper
input:not([type="file"]):read-only.
    .wFormContainer .wForm
.inputWrapper textarea:read-only,
    .wFormContainer .wForm
.inputWrapper
input:not([type="file"]):-moz-read-
only,
    .wFormContainer .wForm
.inputWrapper textarea:-moz-read-
only,
    .wFormContainer .wForm
.inputWrapper
input[type="radio"]:checked + .label
> .input-radio-faux::before,
```

		<pre> .wFormContainer .wForm .inputWrapper input[type="checkbox"]:checked + .label &gt; .input-checkbox-faux::before, .wFormContainer .wfAutosuggest.tt-input </pre>
	Border color for the pop-up calendar outer border	<pre> html .kalendae </pre>
	Border color for the pop-up calendar dates when hovered	<pre> html .kalendae .k-calendar .k-days span.k-active:hover </pre>
	<p>Exceptions</p> <p>Cotton Candy and Sky Themes Only - Border color of buttons</p> <p>Cotton Candy and Sky Themes Only - Border color of page navigation tabs</p>	<pre> .wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton, .wFormContainer .wfTab </pre>
Read Only Text Color	Text color for all read-only inputs (calculation fields and fields marked as no-overwrite with a default value set)	<pre> .wFormContainer .wForm .inputWrapper input:not([type="file"]):read-only, .wFormContainer .wForm .inputWrapper textarea:read-only, .wFormContainer .wForm .inputWrapper input:not([type="file"]):-moz-read- </pre>

		<p>only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper textarea:-moz-read-only</p>
<p>Read Only Background Color</p>	<p>Background color for all read-only inputs (calculation fields and fields marked as no-overwrite with a default value set)</p>	<p>.wFormContainer .wForm</p> <p>.inputWrapper</p> <p>input:not([type="file"]):read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper textarea:read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper</p> <p>input:not([type="file"]):-moz-read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper textarea:-moz-read-only</p>
<p>Read Only Border Color</p>	<p>Border color for all read-only inputs (calculation fields and fields marked as no-overwrite with a default value set)</p>	<p>.wFormContainer .wForm</p> <p>.inputWrapper</p> <p>input:not([type="file"]):read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper textarea:read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper</p> <p>input:not([type="file"]):-moz-read-only,</p> <p>.wFormContainer .wForm</p> <p>.inputWrapper textarea:-moz-read-only</p>

**BUTTONS**

--	--	--

<b>Name of Control</b>	<b>Description of Control</b>	<b>Selectors</b>
Button Font	Font-family for all button text	.wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
Button Font Size	Font-size for all button text	.wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
Button Text Color	Text color of page navigation tabs	.wFormContainer .wfTab
	Background color of the current page of the page navigation tabs	.wFormContainer .wfTab.wfTabCurrentPage
	Text color of the pop-up calendar dates within the active month (month currently selected)	html .kalendae .k-calendar .k-days span.k-in-month.k-active
	Text color of the pop-up calendar selected date (inside or outside of active	html .kalendae .k-calendar .k-days span.k-selected.k-active

	month)	
	Text color of button text	.wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
	<p>Exceptions</p> <p>Demo - Navigation Tab Text Color is controlled by Btn Hover Text Color</p> <p>Demo and Lightning - Current page navigation tab background color is controlled by Main Text Color</p> <p>Lightning Theme Only - Text color of the emphasized fieldset legends (title)</p> <p>Polar and Tag Themes Only - Border color of buttons</p>	
Button Background Color	Background color of page navigation tabs	.wFormContainer .wfTab
	Background color of the pop-up calendar dates within the active month (month currently selected)	html .kalendae .k-calendar .k-days span.k-in-month.k-active

	Background color of the pop-up calendar selected date (inside or outside of active month)	html .kalendae .k-calendar .k-days span.k-selected.k-active
	Background color of buttons	.wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
	Exceptions Lightning only - Background color of emphasized fieldset header	.wFormContainer fieldset.highlighted legend
Button Hover Text Color	Text color of the page navigation tab on hover	.wFormContainer .wfTab:hover
	Text color of the buttons on hover	.wFormContainer .actions .primaryAction:hover, .wFormContainer .wfPagingButtons .wfPageNextButton:hover, .wFormContainer .wfPagingButtons .wfPagePreviousButton:hover
	Exceptions Tag only - Text color of the duplicate field link (ex: "Add Another Response," "Remove")	Tag Only - .wFormContainer .duplicateSpan a:hover Demo Only - .wFormContainer .wfTab

	<p>Demo only - Text color of the page navigation tab</p> <p>Lightning only - Text color of the current page tab of the page navigation</p>	<p>Lightning Only -</p> <p>.wFormContainer</p> <p>.wfTab.wfTabCurrentPage</p>
<p>Button Hover Background Color</p>	<p>Border color of the current page navigation tab</p>	<p>.wFormContainer</p> <p>.wfTab.wfTabCurrentPage</p>
	<p>Background color of the page navigation tab on hover</p>	<p>.wFormContainer</p> <p>.wfTab:hover</p>
	<p>Background color of the buttons on hover</p>	<p>.wFormContainer .actions</p> <p>.primaryAction:hover,</p> <p>.wFormContainer</p> <p>.wfPagingButtons</p> <p>.wfPageNextButton:hover,</p> <p>.wFormContainer</p> <p>.wfPagingButtons</p> <p>.wfPagePreviousButton:hover</p>
	<p>Exceptions</p> <p>Tag only - Background color of the duplicate field link (ex: "Add Another Response," "Remove")</p> <p>Tag only - Border color of the page navigation tab</p> <p>Tag only - Border color of the buttons on hover</p>	<p>.wFormContainer</p> <p>.duplicateSpan a:hover</p> <p>.wFormContainer .wfTab</p> <p>.wFormContainer</p> <p>.wfTab.wfTabCurrentPage</p>
<p>Button Padding Top Bottom</p>	<p>Top and bottom padding for buttons</p>	<p>.wFormContainer .actions</p> <p>.primaryAction,</p> <p>.wFormContainer</p>

		.wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton
Button Padding Left Right	Left and right padding for buttons	.wFormContainer .actions .primaryAction, .wFormContainer .wfPagingButtons .wfPageNextButton, .wFormContainer .wfPagingButtons .wfPagePreviousButton